



G400 Gravel
£ 1,799



E850 Urban Motion
£ 2,399



B400 Urban Low Step
£ 0



M500 ATB Wild
£ 2,349

INFORMACIÓN DEL PRODUCTO

PESO MÁXIMO (CICLISTA + BICICLETA)	150kg	145kg	150kg	120 Kg
PESO	Approx. 19 Kg	26,5kg	Approx. 21 Kg	Approx. 26 Kg

CUADRO

CUADRO	28" Aluminum High Step Frame	28" Aluminium 6061 Low Step Frame	28" Aluminium Low Step Frame	27,5" MTB HARDTAIL - 6061 Hydroformed Aluminum
SUSPENSION	-	-	-	SrSuntour RAIDON34 Boost LOR DS 110 mm 27,5"
DIRECCIÓN	Semi integrated 1-1/8"	Acros Cable Integration AZX585 with IPS / ICR / Block Lock 150°	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS
HORQUILHA	Rigid Alloy 28"	Rigid Alloy Fork 28" with Integrated Cable	Alloy Fork 28"	-

TRANSMISIÓN Y FRENOS

FRENOS	TEKTRO HD-C705 Cable Actuated Hydraulic Road Disc Brake	SHIMANO Hydraulic MT200	ALHONGA Hydraulic Disc HJ-HT474	Shimano Hydraulic MT200
MANETA DE CAMBIO	MICROSHIFT SB-M100A Dual Control Levers 10s	SHIMANO Nexus 8	SHIMANO Altus SL-M2010	SHIMANO DEORE SL-M6000-R 10 Speed
CAMBIO TRASERO	MICROSHIFT AdventX RD-M6205GM 1x10s, Active Motion RD+ with clutch	No	SHIMANO Altus RD-M2000 9S	SHIMANO DEORE 1x10 Speed
CASETE	MICROSHIFT AdventX CS-EH104 11-48, 10s	No	SHIMANO CS-HG201 9S	SHIMANO DEORE 10 Speed
PLATOS	MIRANDA ChainFlow BCD104-38T	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow BCD104-38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T
BIELAS	MIRANDA PSI 170/12	SHIMANO FC-E6100 175mm	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/5
CHAIN	KMC e10 turbo 10s	Chain: SHIMANO NX10	SHIMANO CN-HG53	SHIMANO CN-E6090 10-Speed E-Bike 113 Chain Links
BRAKE ROTOR	SHIMANO SM-RT26M	SHIMANO SM-RT10 180mm	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT10 180mm
FRONT DERRAILEUR	-	-	-	Non applicable

SISTEMA E-BIKE

MOTOR	BAFANG H400B 45N - Rear wheel	SHIMANO Steps E6100	BAFANG H400B 45Nm; Rear Wheel Motor	BROSE DRIVE S 90Nm
BATERÍA	36V 360Wh - Integrada en el tubo inferior - Extraíble	504Wh 36V - Integrado en el tubo de escape - Extraíble	360Wh 36V - Integrated on Downtube - Non Removable	Snake Battery - 504 Wh 36V - Integrada en el tubo inferior - Extraíble
LAVE DE BLOQUEO DE BATERÍA	-	SI	No	SI
CARGADOR	2A - 5 hours total charge time	2A Charger - 7 hours total charge time	2A - 5 hours total charge time	2A charger - 7 hours total charge time
PANTALLA	BAFANG LCD Display DPC11	SHIMANO SC-E6100	BAFANG LCD Display DPC11	Brose Display Allround

JUEGO DE RUEDAS

CUBIERTA	CONTINENTAL Tire 29x2,00 Double Fighter III	28 x 2,2	CONTINENTAL Tire 28x2,00 Contact Cruiser	CONTINENTAL TYRES MOUNTAIN KING 27,5x2.6"
TAMAÑO DE RUEDA	29x2,00	28"	28x2,00	27.5x2.6
LLANTAS	Alloy double wall rim	Alloy Double Wall Rim 25	Alloy double wall rim	Double wall aluminium rims
RADIOS	Stainless stell	Stainless Steel Black	Stainless steel	Stainless Steel Black
BUJE DELANTERO	Alloy quick release M9x100	SHIMANO HB-MT400	Alloy quick release M9x100	SHIMANO HB-MT400-B
BUJE TRASERO	BAFANG H400B	SHIMANO Nexus SG-C6001-8D	BAFANG H400B	SHIMANO FH-M6010-B DEORE

COCKPIT

MANILLAR	SATORI alloy black	Alloy Black Curved 31,8 660mm	SATORI Alloy Black Ø31.8mm - 660mm	FSA V-Drive Flat 740mm / 31.8mm
VÁSTAGO	AHEAD alloy black	Adjustable 90mm with Cable Integration	SATORI Ahead Adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°
PUÑOS	HERRMANS DD36 Ergonomic	Grip GP1-L Nexus/Rohloff 128/93	HERRMANS DD36 Ergonomic	ERGON GA30 BLACK - MTB 128/128

SEGURIDAD Y ACCESORIOS

LUZ DELANTERA	-	SPANNINGA Axendo 40 with reflector	AXA Ecoline 15 with reflector	SI
TIJA DE SILLÍN	ZOOM Alloy Black Ø31,6mm x 300mm	Alloy Black	ZOOM Alloy Black Ø31,6mm x 300mm	FSA ALLOY
CIERRE DE SILLÍN	-	Seatclamp alloy black with quick release	Aleación negra con tornillo 34,9 mm	Seatclamp alloy black with screw
SILLÍN	-	SELLE ROYAL Rio Gel	SELLE ROYAL RIO Gel	SELLE ROYAL Shadow GEL with Black Guards
PEDALES	NECO with reflectors	UNION non-Slip with reflector	NECO with reflectors	Union Ball RingyCity with Retro Reflectors
CERRADURA DEL MARCO	No	Yes - AXA Block XXL	No	-

* Nos reservamos el derecho de modificar la información del producto que aparece en este sitio web sin previo aviso, incluyendo equipos, especificaciones, modelos, colores y materiales.